VANATOO® TRANSPARENT ONE ENCORE PLUS™

WIRELESS POWERED SPEAKER SYSTEM









Key Features

- True 2-way powered speaker system
- Bluetooth wireless connection with AAC and aptX-HD
- Super simple setup in under 5 minutes
- USB, Optical, Coax, and Analog inputs
- Full Featured Remote Control
- Cherry Veneer or Satin Black Finishes
- Magnetically attached Grills
- Auto Input Switching with Silence Detection
- High-Resolution Digital I nputs
- Volume, Bass, Treble Controls
- Vanatoo ClearBass™ Technology
- Subwoofer output with AutoSense
- Low power sleep mode
- Best In Class Bass Response
- Clean, clear mids and highs for superb reproduction
- Customizable Configurations: LED brightness, bass response, subwoofer crossover and level, amp limiters, sleep setting, Bluetooth on/off, more...

Now in their third generation of refinement, the Transparent series of wireless powered speakers from Vanatoo are your solution for high quality music, movie, and game playback without all of the clutter. The integrated Bluetooth makes for easy wireless streaming, and the multiple wired input connections make sure that your computer, phone, tablet, and TV are all supported. The Transparent One Encore *Plus* is the top of the line system, producing surprisingly clean and deep bass. The powerful bass is accompanied by clear and crisp mids, sparkling highs, and palpable imaging that places the musicians in your room. High-end sound quality has never been this easy or affordable.

USB, Toslink Optical, Coaxial, and Analog Inputs

Connect to your computer with the included USB cable, skipping the computer's often troublesome and noisy sound card. Toslink Optical and RCA Coax offer hi-res digital audio connections (96/24) for the best possible reproduction. The analog input allows direct connection to your phone, phono preamp, or other device. Connect with your smart device for voice control with fidelity. The multiple connections give you flexibility while ensuring an obsolete-proof design. Everything connects, everything plays, everything sounds great! Purchase knowing you have years of happy listening ahead.

Bluetooth Wireless Connection

Bluetooth is the standard for wireless streaming from your handheld or computer. Native support for the AAC codec means near-CD quality form your Apple devices, while aptX-HD assures the same for Android users. Listen to your favorite artists from Amazon Prime, Pandora, Spotify, Apple Music, or any of the hundreds of choices at your fingertips. Connecting is a breeze thanks to the Bluetooth control buttons on the wireless remote. Your music, your way.

Full-Featured Remote Control

Take control of your music with the full-featured wireless remote control. Select the source, set the volume, adjust the bass and treble, adjust the subwoofer level, or put the speakers into Bluetooth pairing mode, all from the comfort of your favorite listening position. The remote control makes the T1E *Plus* the ideal addition to a TV, with much better performance than competing soundbars.



VANATOO® TRANSPARENT ONE ENCORE PLUS™


WIRELESS POWERED SPEAKER SYSTEM




Accessories

- · Remote control
- · Magnetically attached grills
- Modular 6 meter long bi-wire interconnect cable
- · USB A to B type cable
- · 3.5mm to 3.5mm mini-jack analog cable
- · 3.5mm mini-jack to RCA analog cable

Active Speaker Rear Panel



Measured Frequency Response



Specifications

Drivers

5.25 inch aluminum cone woofer with 1.2 inch XBL magnetic motor for outstanding performance linearity.

5.25 inch long-throw passive radiator

1.0 inch aluminum dome tweeter with integrated waveguide

Design

2-way bi-amplified active speakers
Assisted passive radiator bass reflex system
6th-Order DSP derived Butterworth response at 48Hz
6th-Order DSP derived Linkwitz-Riley crossover at 2kHz

Inputs

Bluetooth with AAC and aptX-HD for wireless connection USB audio up to 24 bits at 96kHz
Toslink optical up to 24 bits at 96kHz
Coax digital up to 24 bits at 96kHz
Analog conversion at 24 bits at 48Khz

Amplifier & DSP

Direct Digital Class D 100 Watts to each woofer, 20 watts to each tweeter DSP resolution of 24 bits at 48kHz Thermal, short circuit, over current protection

Frequency Response

Flat Mode: 48-20,000 Hz +/- 3dB, -10dB at 38Hz Shelf Mode: Above with -4 dB shelf between 48-150Hz

Subwoofer Crossover

Flat Mode : 4th-Order Butterworth at 80HZ Shelf Mode : 4th-Order Butterworth at 110HZ

Power Requirements

120VAC +/- 10% at 60Hz or 220 VAC +/- 10% at 50Hz

Size

10.0"H x 6.5"W x 8.0"D

Shipping: 18" x 16" x 12" box weighing 30lbs

